

Submittal Data: TM12HKDI 12,000 BTU/H Ceiling Cassette

Job Name _____ Location _____ Date _____

Purchaser _____ Engineer _____

Submitted To _____ For Reference Approval Construction

Unit Designation _____ Schedule No. _____

- GENERAL FEATURES**
- Quiet Operation -Multi-Speed Fan
 - 4-way Discharge Air
 - Internal Condensate Drain Pump
 - Swing Louver
 - Both Wireless & Wired Remote Controllers
 - Power Failure Recovery
 - Sentry Condensate Overflow Protection
 - Decorative Grille



System Ratings

Cooling*	
Rated Capacity	11,946 BTU/H
Heating*	
Rated Capacity	13,652 BTU/H
Sound Pressure (Hi/Lo)**	
Cooling	44/36 dbA
Heating	44/36 dbA
Air Flow (max)	
Indoor Fan	353 CFM

Physical Specifications

Unit Dimensions (LxHxD)	570 x 230 x 570 -mm 22.5 x 9.0 x 22.5-in
Grille Dimensions (LxHxD)	650 x 36 x 650 -mm 25.6 x 1.5 x 25.6 -in
Weight (Net/Shipping)	40/51 LBS

Electrical Ratings

Fan Motor	
Output Power	11 W
FLA	0.2 A
Power Supply	
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz
Voltage Range	187 - 253 V
MCA	1.0 A
Interconnecting Cable Wire Size	14-4 AWG

Units Specification & Data

Air Filter	Netted polypropylene
Condensate Drain Lift (Height)	12-in 305-mm
Drain Size (OD)	1.2-in 31-mm

Refrigerant Piping Data

Refrigerant Type	R410A
Gas Pipe Size (OD)	3/8-in
Liquid Pipe Size (OD)	1/4-in
Connection Method	Flared

* Test conditions are based on AHRI 210/240.
 **Sound Power ratings are per AHRI 270 and AHRI 350



